



## Product Information

### CT 113 High Performance, High Temperature Masking Tape

#### Description:

High performance grade, medium-high adhesion natural colored masking tape for high temperature painting in the transportation industry and for wet sanding applications. An easy-to-unwind, quick-stick tape that resists solvents. Delivers sharp paint lines, removes cleanly without residue or paint flake, and can be used in temperatures up to 300°F (149°C).

#### Application:

- For high temperature paint masking and metal fabrication applications in the transportation (auto, coaches, buses, and marine) industry.
- Also used for wet sanding applications.
- Recommended for indoor use only.

Meets Standards: ASTM D 6123/D 6123M-97 (2012), Type 1

Technical Data	
Adhesive	Rubber-Based
Substrate	Smooth Crepe Paper
Thickness (mils)	5.8 (0.15 mm)
Adhesion to Steel (oz/in of width)	43 (4.71 N/10mm)
Tensile Strength (lbs/in of width)	26 (45.5 N/10mm)
Elongation (% at Break)	9
Service Temperature	45°F to 300°F (7.2°C to 149°C)

*The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.*

Carolina Tape & Supply Corporation  
502 19th St. Pl. SE, Hickory, NC 28602  
Phone: 800-237-6079  
Fax: 828-322-7268  
[www.carolinatape.com](http://www.carolinatape.com)

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.