



## Product Information

### CT 183 Utility Grade, High Adhesion Masking Tape

#### Description:

Utility grade, high adhesion natural colored masking tape for general purpose packaging, bundling, holding, splicing, tabbing, and banding applications involving a variety of substrates. Economical tape solution that offers quick stick and flexibility. Water and oil resistant.

#### Application:

- For general purpose packaging, bundling, holding, splicing, tabbing, and banding applications involving a variety of substrates.
- Not recommended for exacting industrial masking, spray painting, or oven-baking applications.

Meets standards: ASTM D 6123/D 6123M-97 (2012), Type 1

Technical Data	
Adhesive	Synthetic Rubber-Based
Substrate	Crepe Paper
Thickness (mils)	5 (0.13 mm)
Adhesion to Steel (oz/in of width)	49 (5.36 N/10mm)
Tensile Strength (lbs/in of width)	20 (35 N/10mm)
Elongation (% at Break)	8
Service Temperature	50°F to 150°F (10°C to 66°C)

*The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.*

Carolina Tape & Supply Corporation  
502 19th St. Pl. SE, Hickory, NC 28602  
Phone: 800-237-6079  
Fax: 828-322-7268  
[www.carolinatape.com](http://www.carolinatape.com)

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.