



Product Information

CT 305 Acrylic Transfer Adhesive

Description:

High performance acrylic transfer adhesive specifically designed to provide excellent adhesion and long term aging on a wide variety of urethane foams. The product is supplied with a 76# polycoated release liner. Offers ultra high anchorage to a variety of urethane foams and good adhesion to many metals and plastics. Performs well over a wide temperature range. Offers extremely high tack, quick-stick, and peel strength; excellent humidity and water resistance; and good chemical resistance.

Application:

- Assembly aid and splicing
- Foam fabrication and EPDM lamination

Technical Data

Adhesive	Acrylic
Substrate	76# Polycoated
Thickness (mils)	5 (0.127 mm)
Adhesion to Steel (oz/in of width)	147 (41 N/25mm)
Application Temperature	65°F (18°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602

Phone: 800-237-6079

Fax: 828-322-7268

www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.