



Product Information

CT 324 5.9 Mil Utility Double-Coated Vinyl Tape

Description:

Thin, flexible vinyl (PVC) film coated on both sides with an aggressive pressure-sensitive natural rubber adhesive. Excellent adhesion properties and good initial tack allow immediate, permanent bonding to a variety of surfaces (including irregular and porous surfaces). Features an easy release treated/moisture resistant flatback liner (white).

Application:

- Mounting novelties and promotional items.
- Sign positioning, splicing, carpet tape (hold-down and position).
- Mirror manufacturing, engravers (temporary holding), insulation (holding for metal building construction), and any application that requires the joining of two surfaces.

Technical Data

<i>Adhesive</i>		Natural Rubber/Resin
<i>Substrate</i>		Vinyl (PVC) Film
<i>Thickness (mils)</i>	With Liner	9.5 (0.24 mm)
	Without Liner	5.9 (0.15 mm)
<i>Adhesion to Steel (oz/in of width)</i>		55 (15 N/25mm)
<i>Quick Stick to Steel (oz/in of width)</i>		28 (7.7 N/25mm)
<i>Tensile Strength (lbs/in of width)</i>		15 (66 N/25mm)
<i>Elongation (% at Break)</i>		30

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.