



Product Information

CT 326 Double-Coated UPVC Film Tape

Description:

Double-coated UPVC film with an exceptionally high tack, high peel, acrylic adhesive. Bonds well to rough or porous surfaces and exhibits excellent adhesion to ether and ester foams. Offers resistance to environmental extremes and allows conformability. Supplied with a 60# kraft release liner.

Application:

- Lamination to EPDM rubber, plastics, glass, and urethane foams.
- Difficult bonding and splicing applications.
- Product assembly.

Technical Data

<i>Adhesive</i>		Acrylic
<i>Substrate</i>		UPVC Film
<i>Thickness (mils)</i>		8.5 (0.216 mm)
<i>Liner (mils)</i>		3.5 (.089 mm)
<i>Adhesion to Steel (oz/in of width)</i>	Exposed	136 (37.8 N/25mm)
	Liner	135 (37.8 N/25mm)
<i>Operating Temperature</i>		-40°F to 200°F (-40°C to 93°C)
<i>Application Temperature</i>		65°F (18°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.