



Product Information

CT 352

Double-Coated Medium Density Foam Tape

Description:

1/8", double-coated, medium density closed cell PVC foam tape with a rubber adhesive. It offers UV resistance and sound dampening properties. The foam density permits clean die cuts and faster penetration. Available in different thicknesses.

Application:

- Sound dampening, gasketing, shock absorption cushion
- Standard two-sided adhesive glazing tape
- Displaces wet sealant and butyls
- Excellent strength and wear resistance

Meets Spec: AAMA

Technical Data

<i>Adhesive</i>	Rubber
<i>Substrate</i>	PVC Foam
<i>Thickness (mils)</i>	1/8"
<i>Elongation (% at Break)</i>	160
<i>Tensile Strength (lbs/in of width)</i>	80 (550 kPa)
<i>Application Temperature</i>	50°F to 100°F (10°C to 45°C)
<i>Service Temperature</i>	-30°F to 200°F (10°C to 90°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602

Phone: 800-237-6079

Fax: 828-322-7268

www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.