



Product Information

CT #917

14 Mil PTFE Coated Glass Fabric Tape

14 mil PTFE coated woven fiberglass tape with acrylic adhesive. Is dimensionally stable, possesses excellent tensile strength, and has exceptional wear life. Preferred for most adhesive applications where a smooth surface with excellent nonstick properties is required.

Also available in 3 mil thick (#913), 5 mil thick (#914), 6 mil thick (#915), and 10 mil thick (#916).

Application:

- Designed to operate in demanding temperatures and chemical environments
- Unique properties of PTFE are joined with exceptional strength and durability of glass fabric making it ideally suited for a variety of industries including packaging, aerospace, and electronics

TECHNICAL DATA

Adhesive	Acrylic
Substrate	PTFE Coated Glass Fabric
Thickness	15.5 Mils (0.394 mm)
Adhesion to Steel	90 oz/in (52.20 N/5cm)
Tensile Strength	500 lbs/in (892.86 N/cm)
Operating Temperature	-40°F to 350°F (-40°C to 177°C)
Dielectric Strength	9,000 Volts

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.