



Product Information

CT #606

Dead Soft Printed Aluminum Foil

606 is a 2 mil, dead soft printed aluminum foil with an acrylic adhesive.

Meets Specs: AFTS-100-93; UL 181A-P Listed, Flame Spread Index-25, Smoke Development Index-50.

Application:

- To make fiberglass duct board joins and seams air tight
- Resists vapors and other contaminants

TECHNICAL DATA

Adhesive	Acrylic
Substrate	Dead Soft Aluminum Foil
Thickness	6.8 Mils (0.17 mm)
Adhesion to Steel	70 oz/in (7.66 N/10mm)
Tensile Strength	25 lbs/in (43.8 N/10mm)
Elongation (% at Break)	2
Service Temp. Min	-20°F (-29°C)
Service Temp. Max	260°F (127°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.