



Product Information

CT #612

Insulated All Surface Jacket Tape

612 is an insulated, HVA ASJ with an all temperature acrylic adhesive and UL Listed backing.

Meets Spec: UL Listed

Application:

- Butt joint cold and dual temp duct and pip systems and seal seams in pipe covering

TECHNICAL DATA

Adhesive	Acrylic, All Temperature
Substrate	All Surface Jacket

Thickness	12.6 Mils (0.32 mm)
------------------	------------------------

Adhesion to Steel	80 oz/in (8.76 N/10mm)
--------------------------	---------------------------

Tensile Strength	50 lbs/in (87.6 N/10mm)
-------------------------	----------------------------

Elongation (% at Break)	6.7
-----------------------------------	-----

Service Temp. Min	-20°F (-29°C)
--------------------------	---------------

Service Temp. Max	260°F (127°C)
--------------------------	---------------

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.