



Product Information

CT #436

High Performance Polyester Film Tape

436 is a 2 mil polyester film tape with a high performance silicone adhesive that provides clean removal.

Application:

- Masking in powdered painting applications
- Provides clean removal from powdered coated surfaces

TECHNICAL DATA

Adhesive	High Performance Silicone
Substrate	Polyester Film

Thickness	3.5 Mils (0.089 mm)
------------------	------------------------

Adhesion to Steel	46 oz/in
--------------------------	----------

Tensile Strength	55 lbs/in
-------------------------	-----------

Elongation (% at Break)	Above 70
-----------------------------------	----------

Temperature Class	130°C
--------------------------	-------

Dielectric Strength	8,000 Volts
----------------------------	-------------

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.