



## Product Information

### CT #413

### Polyester Silicone Splicing Tape

413 is a 1.5 mil polyester film tape with a 1 mil, pre-cured silicone adhesive and is available in different colors. It is electrically and mechanically stable at operating at high temperatures.

#### Application:

- Used for splicing of silicone-coated papers
- Designed to perform in all phases of the masking of PCB production

#### TECHNICAL DATA

<b>Adhesive</b>	Pre-cured Silicone
<b>Substrate</b>	Polyester Film

<b>Thickness</b>	2.5 Mils (0.0635 mm)
------------------	-------------------------

<b>Adhesion to Steel</b>	40 oz/in (11 N/25mm)
--------------------------	-------------------------

<b>Tensile Strength</b>	28 lbs/in
-------------------------	-----------

<b>Elongation</b> (% at Break)	115
-----------------------------------	-----

<b>Temperature Resistance</b>	400°F (204°C)
-------------------------------	---------------

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation  
502 19<sup>th</sup> St PL SE, Hickory, NC 28602  
Phone: 800-237-6079  
[www.carolinatape.com](http://www.carolinatape.com)

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.