



Product Information

CT #955

General Purpose Dead Soft Aluminum Foil Tape

955 is a general purpose, 1.6 mil dead soft aluminum foil tape with an extremely aggressive clear acrylic adhesive and a 3 mil release liner.

Meets Specs: UL 510, Section 4 for Flammability.

Application:

- For use on variety of flat, irregular, or curved surfaces for non-critical applications such as sealing out dust and moisture, masking, and duct sealing
- Bonds tightly and permanently to insulation facing and HVAC
- Performs well over a wide range of environmental conditions

TECHNICAL DATA

Adhesive	Acrylic
Substrate	Dead Soft Aluminum Foil
Thickness	3.1 Mils (0.079 mm)
Adhesion to Steel	90 oz/in (9.9 N/cm)
Tensile Strength	12.5 lbs/in (22 N/cm)
Elongation (% at Break)	3.5
Service Temperature	0°F to 150°F (-18°C to 66°C)
Minimum Application Temperature	-25°F (-31.7°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.