



Product Information

CT #773

UV-Stabilized Polyethylene Film Tape

773 is a clear, medium density, UV-stabilized polyethylene tape with an aggressive, non-yellowing acrylic adhesive. It is a tough abrasion resistant tape for indoor/outdoor use and removes cleanly.

Application:

- Tough abrasion resistant tape for indoor/outdoor patching, seaming, and over laminating applications where protection from moisture, solvents, and chemical exposure is critical
- Removes cleanly leaving no residue
- Will not crack, crease, or break down after extended periods of use
- Invisible on most surfaces

TECHNICAL DATA

Adhesive	Non-Yellowing, Aggressive Acrylic
-----------------	-----------------------------------

Substrate	Clear Polyethylene
------------------	--------------------

Thickness	5.5 Mils (0.14 mm)
------------------	--------------------

Adhesion to Steel	32 oz/in (3.5 N/cm)
--------------------------	---------------------

Tensile Strength	11 lbs/in (19.26 N/cm)
-------------------------	------------------------

Elongation (% at Break)	500%
-----------------------------------	------

Operating Temperature	-40°F to 200°F (-40°C to 93°C)
------------------------------	--------------------------------

Application Temperature	50°F to 120°F (10°C to 49°C)
--------------------------------	------------------------------

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.