



Product Information

CT #713

High Performance Grade BOPP Film

713 is a high performance grade, 40 µm biaxially-oriented polypropylene film with a synthetic rubber/resin hot melt adhesive.

Meets Specs: CID-A-A-1684C; ASTM-D1974; ASTM D-5486M; AFTS-100-93.

Application:

- Recommended for large, bulky, or heavy cartons
- Manual or high speed automated carton sealing in moderate to severe handling environments
- Excellent for high speed critical closure situations

TECHNICAL DATA

Adhesive	Synthetic Rubber/Resin Hot Melt
Substrate	40 µm BOPP Film

Thickness	2.5 Mils (0.06 mm)
------------------	-----------------------

Adhesion to Steel	54 oz/in (5.91 N/10mm)
--------------------------	---------------------------

Tensile Strength	33 lbs/in (57.8 N/10mm)
-------------------------	----------------------------

Elongation (% at Break)	150
-----------------------------------	-----

Service Temperature	-20°F to 150°F (-29°C to 66°C)
----------------------------	-----------------------------------

Application Temperature	35°F to 110°F (2°C to 43°C)
--------------------------------	--------------------------------

Holding Power to Fiberboard	25,000+ minutes
------------------------------------	-----------------

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.