



Product Information

CT #895

Flexible Fine Cell Gasketing Foam Tape

895 is a 3/8 inch thick, flexible fine cell foam tape (1.3 pound density) designed for automotive gasketing applications, especially for RV doors. The high-tack permanent rubber-based pressure sensitive adhesive exhibits a superior balance of tack, peel, and holding power on a wide variety of surfaces. 895 offers resistance to water and moisture, has very good air permeability, and remain flexible over a long period of demanding usage. It is also available in other thicknesses.

Application:

- Uniform and breathable without voids or tears
- Resists aging, weather, and environmental damage over long term
- Automotive and RV door gasketing

TECHNICAL DATA

Adhesive	Rubber-Based
Substrate	Fine Cell Polyether Urethane Foam
Thickness	375 Mils (9.525 mm)
Adhesion to Steel	128 oz/in
Tensile Strength	12 to 15 lbs/in
Elongation (% at Break)	140
Application Temperature	50°F to 80°F (10°C to 26.7°C)
Functional Temperature	0°F to 140°F (-17.8°C to 60°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.