



Product Information

CT #875

SCE 41 Neoprene/EPDM/SBR Closed Cell Foam Tape

875 is a 1/8" thick SCE 41, neoprene/EPDM/SBR black closed cell foam tape (6 to 11 pound density) with a high tack rubber-based adhesive on one side with easy-to-use release liner. It is also available in 3/16" thick (#876), 1/4" thick (#877), and 5/16" thick (#878).

Application:

- Meets most standard specs for closed cell stock
- Used for cushioning, sound, and vibration dampening, gasketing, insulation, shock absorption, dust proofing, sealing, and weather stripping

TECHNICAL DATA

Adhesive	Rubber-Based
Substrate	SCE 41 Neoprene/EPDM/ SBR
Thickness	125 Mils (3.175 mm)
Tensile Strength	75 lbs/in
Elongation (% at Break)	150
Service Temperature	-40°F to 250°F (-40°C to 121.1°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.