



Product Information

CT #855

SCE 42 Neoprene/EPDM/SBR Tape

855 is a 3/16" thick SCE 42 Neoprene/EPDM/SBR tape with a black closed cell backing (5 to 7 pound density) and high-tack, rubber-based pressure sensitive adhesive on one side with easy-to-use release liner. It is also available in 1/8" thick (#854), 1/4" thick (#856), and 1/16" thick (#857).

Application:

- Conformable, compressible, and highly flexible product for cushioning, sound, and vibration dampening, gasketing, weather stripping, dust proofing, shock absorption, and sealing

TECHNICAL DATA

Adhesive	Rubber-Based
Substrate	Black Closed Cell Neoprene/EPDM/SBR
Thickness	187.5 Mils (4.76 mm)
Adhesion to Steel	128 oz/in
Tensile Strength	100 lbs/in (689.5 kPa)
Elongation (% at Break)	150
Functional Temperature	0°F to 140°F (-17.8°C to 60°C)
Application Temperature	50°F to 80°F (10°C to 26.7°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.