



## Product Information

### CT #835

#### Closed Cell PVC Foam Tape

835 is a 3/16" thick, 15 lb density, single-coated, closed-cell PVC foam with an acrylic adhesive and paper release liner. It is also available in 1/8" thick (#834), 1/4" thick (#836), and 1/16" thick (#869).

Meets Spec: AAMA 810.1-85 expand cellular glazing.

#### Application:

- Excellent choice for high performance glazing applications

#### TECHNICAL DATA

<b>Adhesive</b>	Acrylic
<b>Substrate</b>	Single-Coated Closed-Cell PVC Foam
<b>Thickness</b>	187.5 Mils (4.76 mm)
<b>Tensile Strength</b>	22 lbs/in
<b>Elongation (% at Break)</b>	160
<b>Service Temperature</b>	-40°F to 180°F (-40°C to 82°C)
<b>Application Temperature</b>	50°F to 110°F (10°C to 45°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation  
502 19<sup>th</sup> St PL SE, Hickory, NC 28602  
Phone: 800-237-6079  
[www.carolinatape.com](http://www.carolinatape.com)

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.