



## Product Information

### CT #839

### General Purpose, UV-Resistant Closed Cell PVC Foam Tape

839 is a general purpose, 3/8" thick, 7 pound density, single-coated, UV-resistant closed cell PVC foam tape with an acrylic adhesive and paper release liner. It is also available in 1/4" thick (#837), 1/8" thick (#838), 3/16" thick (#841), 1/2" thick (#842), 1/16" thick (#843), 3/4" thick (#873), and 3/8" thick flame retardant (#868).

Meets Specs: General Motors 6086M-IA; Ford ESB M3G102-A; Chrysler MSAY 511-A, B and C.

#### Application:

- Economical tape used as weather stripping, gasketing, and applications requiring positive seals on irregular surfaces
- Flexible and conformable to seal tight radius curves when critical
- Seals out air, moisture, light, and dust when compressed at least 30%
- Resists most chemicals, acids, and solvents

Carolina Tape & Supply Corporation  
502 19<sup>th</sup> St PL SE, Hickory, NC 28602  
Phone: 800-237-6079  
[www.carolinatape.com](http://www.carolinatape.com)

#### TECHNICAL DATA

<b>Adhesive</b>	Acrylic
<b>Substrate</b>	Single-Coated Closed-Cell PVC Foam
<b>Thickness</b>	375 Mils (9.525 mm)
<b>Tensile Strength</b>	25 lbs/in
<b>Elongation (% at Break)</b>	150
<b>Service Temperature</b>	-40°F to 180°F (-40°C to 82°C)
<b>Application Temperature</b>	50°F to 110°F (10°C to 45°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.