



## Product Information

### CT #844

### Premium Grade Single-Coated Urethane Foam Tape

844 is a premium grade, 1/32" thick, high density, sing-coated, off-white color cellular urethane foam with an aggressive acrylic adhesive and a 60 pound density Kraft glassine release liner. It is also available in 1/16" thick (#845) and 1/8" thick (#846).

Meets Spec: UL 746C

#### Application:

- Economical tape used as weather stripping, gasketing, and applications requiring positive seals on irregular surfaces
- Flexible and conformable to seal tight radius curves when critical
- Seals out air, moisture, light, and dust when compressed at least 30%
- Resists most chemicals, acids, and solvents

#### TECHNICAL DATA

<b>Adhesive</b>	Acrylic
<b>Substrate</b>	Single-Coated Cellular Urethane Foam
<b>Thickness</b>	30 Mils (0.762 mm)
<b>Adhesion to Steel</b>	80 oz/in
<b>Tensile Strength</b>	200 lbs/in
<b>Elongation (% at Break)</b>	340

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation  
502 19<sup>th</sup> St PL SE, Hickory, NC 28602  
Phone: 800-237-6079  
[www.carolinatape.com](http://www.carolinatape.com)

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.