



Product Information

CT #505

Extra Strength Polypropylene Filament Tape

505 is an extra strength, fiberglass reinforced, polypropylene filament tape with a hot melt rubber adhesive used for the most demanding industrial applications.

Application:

- Most demanding industrial strapping, palletizing, and unitizing applications where a high performance tape is required

TECHNICAL DATA

Adhesive	Hot Melt Rubber
-----------------	-----------------

Substrate	Fiberglass Reinforced Polypropylene
------------------	---

Thickness	6.2 Mils (0.157 mm)
------------------	------------------------

Adhesion to Steel	77 oz/in (21 N/25mm)
------------------------------	-------------------------

Tensile Strength	350 lbs/in (1532 N/25mm)
-----------------------------	-----------------------------

Elongation (% at Break)	4
-----------------------------------	---

Shear to Kraft Paper (hours)	> 96
--	------

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.