



Product Information

CT #503

Medium Strength PET Strapping Tape

503 is a medium strength, fiberglass reinforced, polyester strapping tape with a solvent-based rubber adhesive.

Application:

- General purpose strapping, palletizing, and unitizing applications where a medium strength tape is needed

TECHNICAL DATA

Adhesive	Solvent-Based Rubber
Substrate	Fiberglass Reinforced Polyester
Thickness	5.6 Mils (0.14 mm)
Adhesion to Steel	39 oz/in (10.7 N/25mm)
Tensile Strength	175 lbs/in (766 N/25mm)
Elongation (% at Break)	4
Operating Temp. Min	40°F (4°C)
Operating Temp. Max	200°F (93°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.